



GLC Industrial
Made to Perform™



GLC CalPro™ 450

Product Codes

Bulk: 604G

Ingredients

Calcium Carbonate

CaCO₃

TYPICAL CHARACTERISTICS

Moisture (max) 0.5%

Bulk Density (approx.) lbs/cu.ft.

Compact: 100 lbs/cu.ft.

Loose: 86 lbs/cu.ft.

GLC MINERALS' HIGH-CALCIUM LIMESTONE

Use in combination with GLC Minerals' dolomitic limestone MagPro™ products to streamline your glass production process.

SOURCED IN THE USA

Chemistry is specifically selected from mines in the United States for use in the glass industry.

GUARANTEED QUALITY

Cal Pro™ is produced at in an ISO 9001:2015 certified facility.

TYPICAL CHEMICAL ANALYSIS

Chemical Compound	% of sample
Calcium Carbonate — CaCO ₃	97.0
Magnesium Carbonate — MgCO ₃	2.0
Aluminum Oxide — Al ₂ O ₃	0.15
Iron Oxide — Fe ₂ O ₃	0.13
Silicon Dioxide — SiO ₂	0.3

GLC Minerals, LLC (10015318) has been certified by DQS Inc. to **ISO 9001:2015**.

TYPICAL PARTICLE SIZE DISTRIBUTION

U.S. Mesh Screen	% Retained	% Passed
10	0	100
16	0	100
20	9	91
30	27	64
50	34	30
100	18	12
140	6	6
200	2	4
Pan	4	0