



**GLC Industrial**  
Made to Perform™



# GLC CalPro™ 450

## Product Codes

Bulk: 604G

## Ingredients

Calcium Carbonate

**CaCO<sub>3</sub>**

### TYPICAL CHARACTERISTICS

**Moisture (max)** 0.5%

**Bulk Density (approx.) lbs/cu.ft.**

Compact: 100 lbs/cu.ft.

Loose: 86 lbs/cu.ft.

## GLC MINERALS' HIGH-CALCIUM LIMESTONE

Use in combination with GLC Minerals' dolomitic limestone MagPro™ products to streamline your glass production process.

### SOURCED IN THE USA

Chemistry is specifically selected from mines in the United States for use in the glass industry.

### GUARANTEED QUALITY

Cal Pro™ is produced at in an ISO 9001:2015 certified facility.

### TYPICAL CHEMICAL ANALYSIS

Chemical Compound	% of sample
Calcium Carbonate — CaCO <sub>3</sub>	97.0
Magnesium Carbonate — MgCO <sub>3</sub>	2.0
Aluminum Oxide — Al <sub>2</sub> O <sub>3</sub>	0.15
Iron Oxide — Fe <sub>2</sub> O <sub>3</sub>	0.13
Silicon Dioxide — SiO <sub>2</sub>	0.3

GLC Minerals, LLC (10015318) has been certified by DQS Inc. to **ISO 9001:2015**.

### TYPICAL PARTICLE SIZE DISTRIBUTION

U.S. Mesh Screen	% Retained	% Passed
10	0	100
16	0	100
20	9	91
30	27	64
50	34	30
100	18	12
140	6	6
200	2	4
Pan	4	0